

PORTABLE AIR HEATERS ELECTRIC



B 2
B 3



B 2PTC
B 3PTC



B 5
B 9
B 15
B 22



Optional accessories



Extension cord
B 5, B 9 – 5m
B 5, B 9 – 10m
B 15, B 22 – 5m
B 15, B 22 – 10m



Features

- Automatic reset
- Built-in room thermostat
- No oxygen consumption
- No fumes, no odours, no humidity
- Summer-Winter switch for ventilation only
- Low noise
- Motor with thermal protection
- Overheat thermostat
- Adjustable heat

Applications

- Construction sites
- Workshop and warehouse space heating
- Agriculture
- Events and military
- Homes and offices
- Cellars



Specifications	Units	B 2PTC	B 3PTC	B 2	B 3	B 5	B 9	B 15	B 22
Heating power	kW	1/2	1.5/3	1/2	1.65/3	2.5/5	4.5/9	7.5/15	11/22
	Btu/h	3400-6800	3400-10200	3400-6800	5630-11260	8530-17000	515350-30700	25600-51200	37530-75100
	kcal/h	860-1720	860-2580	860-1720	1430-2860	2150-4300	3870-7740	6450-12900	9460-18900
Air flow	m ³ /h	97	97	184	510	510	800	1700	2400
Power supply	V/Hz	230/1ph/50	230/1ph/50	230/1ph/50-60	230/1ph/50-60	400/3ph/50	400/3ph/50	400/3ph/50	400/3ph/50-60
Plug (male) from heater side		16A/3P	16A/3P	16A/3P	16A/3P	16A/5P	16A/5P	32A/5P	32A/5P
Rated current	A	8.7	13	8.7	14.5	7.2	13	22	32
Switch pos. 1		1 kW	Off	Off	Off	Off	Off	Off	Off
Switch pos. 2		2 kW	1.5kW	Fan	Fan	Fan	Fan	Fan	Fan
Switch pos. 3/4	kW	-	3	1.0/2.0	1.65/3.3	2.5/5.0	4.5/9.0	7.5/15	11.0/22.0
Thermostat control		Included	Included	Included	Included	Included	Included	Included	Included
Temperature range	°C	0-40	0-40	5-35	5-35	5-35	5-35	5-35	5-35
Protection		IP21	IP21	IP24	IP24	IP24	IP24	IP24	IP24
Product size (l x w x h)	mm	200 x 200 x 200	244 x 240 x 250	220 x 200 x 330	260 x 260 x 410	310 x 360 x 380	340 x 420 x 440	350 x 470 x 490	350 x 540 x 590
Weight	kg	1.9	3.4	3.7	5.1	6.4	9.3	15.0	20.0
110 V		No	No	No	Available	No	No	No	No

Get In Touch

Call: 0845 6880112
Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH