

# INDUSTRIAL DRYING ADSORPTION



**DT 800**  
**DT 1100**



## Features

- Sturdy housing in stainless steel
- Controls including, humidity sensor operation, alarm system, and different options for dry air fan operation
- PTC (Positive Temperature Control) reactivation heater, eliminates the risk of overheating and allows step-less capacity control

## Optional accessories

- Air cooled condenser
- DDC controls

## Applications



- Process air systems
- Store rooms
- Pharmaceutical production
- Pumping stations
- Film production
- Electronics manufacturing
- Confectionery and food production
- Museums and art galleries
- Cold storage

Specifications	Units	DT 800	DT 1100
Dehumidification @ 20°C/60% RH	kg/h	4.4	6.0
Dry air flow	m <sup>3</sup> /h	800	1100
Available pressure	Pa	150	200
Wet air flow	m <sup>3</sup> /h	250	370
Available pressure	Pa	175	200
Power consumption	kW	7	10
Power supply	V/Hz	400/3ph/50	400/3ph/50
Sound level	dB(A)	60	62
Reactivation power	kW	6.7	9.25
Electrical (E), steam (S), gas (G) react. option		E	E
Filter class		3	3
Product size (l x w x h)	mm	1050 x 600 x 690	1050 x 600 x 690
Weight	kg	80	80

## Get In Touch

Call: 0845 6880112  
Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

## Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH